

# "Mounting Suggestions Harley-Davidson® Dyna Glide & "Dyna Wide Glide 1996- 2005 "Two-Piece Seat

#### Tools Required:

- Phillips Screwdriver
- Allen Wrench Set

#### Hardware:

- Stock Rear Fender Screw
- Solo Seat
- Nut Insert Kit w/Instructions (Included)
   Passenger Seat
  - Chrome Mounting Bracket (Included)
  - Chrome 1/4"-20 Ăllen Bolt (Încluded)



#### **Baseplate Features:**

Solo and passenger seat feature formed steel baseplate with polyurethane bumpers strategically located to prevent them from touching the frame and to minimize vibration.

NOTE: Mustang Passenger Seats work ONLY with Mustang Solo Seats.

#### **Removal of Stock Seat**

- Remove rear fender screw and set aside. The stock rear fender screw will be used to attach your new Mustang Seat.
- 2. If applicable, remove seat strap.
- 3. Slide seat back and lift up to remove.

### **Mounting of Mustang Solo**

- Install nut insert kit if needed. Note: Spool washer shown is used for rear seat mounting only. (Fig. I)
- 2. Engage nose tab of seat into frame.
- 3. Align chrome rear tab with threaded mount in fender.
- 4. Secure the rear of the solo seat to the fender with stock fender screw to complete the installation process.

Fig. I





Solo with matching fender bib

## **Mounting of Mustang Passenger Seat**

- 1. Remove screw from rear of solo.
- 2. Align spool washer on top of the solo bracket and bolt down to the fender with the supplied bolt.
- Secure rear bracket to baseplate of passenger seat with supplied screws. Use the set of holes closest to the rear of the seat for all Dyna Wide Glide models and second set of holes for all Dyna Glide models. (Fig. I)
- 4. Engage slotted bracket on the front of the passenger seat into spool washer. (Fig. II)
- 5. Secure rear of passenger seat to fender with stock screw which was removed from solo. *NOTE: If mounting on a model without the fender clip nut as shown (Fig. III), use the supplied shoulder washer.*

Fig. I



Bracket shown in Dyna Wide Glide Position

Fig. II



# **Enjoy the Comfort of your new Mustang Seat!**



Fig. III



These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.comÈ