



www.GRAVESPORT.com
Tel (818) 902-1942 Fax (818) 902-3821

*7629 Densmore Avenue
Van Nuys, CA 91406*

FEB-10S1RR-K

**Fender Eliminator
2010-2017 BMW S1000RR**



Note orientation of bracket: widely spaced holes align with undertail, license plate surface is offset and mounting holes for plate sit above where the bracket attaches to undertail

- 1) Remove the passenger seat and unplug the turn signal wiring harness.
- 2) Remove the fender.
- 3) Remove the turn signal lenses and unplug the turn signal lights and pull out the wires. Label the wires left and right for reference when reassembling.
- 4) Remove the turn signals from the fender.
- 5) Loosen the license plate light nuts and remove the light.
- 6) Unplug the light socket from the housing.
- 7) Remove the wiring from the stock fender.

- 8) Install turn signals onto fender eliminator.
- 9) Install the wiring into the fender eliminator noting the left and right signals marked earlier. Left installs on the left, Right installs on the right.
- 10) Install the license plate light in the downward facing position.
- 11) Bolt fender eliminator onto motorcycle using stock bolts. Plug into the wiring harness.
- 12) Bolt the license plate onto the fender eliminator.

NOTE: TEST ALL TURN SIGNAL LIGHTS BEFORE RIDING YOUR MOTORCYCLE.

Be sure to re-install the turn signals on the correct sides of the fender eliminator.

After installation, double check to be sure that the rear turn signals work accordingly.

If the turn signals are installed on the wrong sides they will work in reverse.

The purchaser releases Graves Motorsports, Inc from all liabilities pertaining to the installation and use of purchased parts. Purchaser recognizes that any alteration and/or modifications to the vehicle may increase the risk of injury or accident. This product is intended for Closed Course Competition Use Only and may render the vehicle illegal for use on public roads.