



MOUNTING SUGGESTIONS:

Honda VT750C2 Spirit (Shaft) & Phantom 2007-2017 - One-piece Seat

Hardware:	Stock fender bolt
Tools needed:	Metric Allen wrenches

Removal of stock seat:

1. Locate and remove the two side mount screws using a Metric Allen wrench. These are not needed to mount your Mustang seat.



2. Remove the rear fender bolt with a Metric Allen wrench. This bolt will be used to mount your Mustang seat.

3. Lift seat up and back to remove from motorcycle.

Installation of Mustang seat:

1. Slide the front nose tab under the gas tank.

2. Align the rear tab with the fender hole.

3. Secure the rear bracket to the fender with the stock bolt.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part number: 76166

**You are cordially invited to
— Tour the Mustang Factory —**

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.