



Installation and User Instructions

Description:	Tank Bag	Model:	See Parts List
Part-Number:	K57003-109/110/111/112/113/114/115	Approximate Assembly Time:	15 min

Before you begin installation, read through the installation instructions and check to be sure all parts are present.

If you are in doubt as to any part of the installation, please ask your authorized Kawasaki dealer to complete the installation. Please note that Kawasaki cannot assume any responsibility for damage resulting from incorrect installation.

Parts List				Notes/Tools Required:
Seq.	Part Number	Description	Qty.	1. See Owner's Manual for seat removal
1.	K57003-109	Ninja 250R, 08-12	1	
2.	K57003-110	Ninja 650R, 09-11	1	
3.	K57003-111	Ninja 650, 2012-2013	1	
4.	K57003-112	Versys, 08-14	1	Not compatible with 99994-0193 Grip Heaters
5.	K57003-113	Ninja 1000, 11-14	1	
6.	K57003-114	Ninja 300, 13-14	1	
7.	K57003-115	Concours 14, 2010-2014	1	

All Tank Bags

WARNING

- Do not load bag with more than 5 lbs (2kg).
- Do not exceed the maximum vehicle load. Review your vehicle owner's manual for information regarding proper loading.
- Before riding, make sure the bag is securely attached and the lid is zipped closed.

Ninja 1000

WARNING

Do not adjust the windshield angle while riding.
Do not turn the handlebars while adjusting the windshield angle.
Read the OWNER'S MANUAL before adjusting the windshield angle.

NOTICE

Do not store temperature or moisture sensitive devices in the tank bag or lid tray.
Tank bag is only water-resistant; take care to protect cargo in rainy weather.
Carefully clean the fuel tank mounting surfaces and the underside of the tank bag before each ride.
Kawasaki cannot be responsible for any damage to the fuel tank finish or devices stored in the tank bag
Do not store magnetic data devices in bottom of tank bag or allow such devices to come in contact with magnets.
Do not use on satin, semi-gloss or flat finish fuel tank surfaces

Installation Preparation

All Models except Concours 14

1. Refer to the motorcycle Owner's Manual and remove driver seat.
2. Position the tank bag onto the fuel tank and note where the front straps and skirt material come in contact with any painted plastic surfaces. To prevent damage to the painted surfaces, apply the clear adhesive decal material in these areas. Now refer to the model specific applications below-
3. Remove backing from hook&loop patch and apply the adhesive side to the upper side of the front seat bracket located on top of the fuel tank rear mount. Allow the adhesive to set for 24 hours before using the tank bag or removing it.

NOTE

For Ninja 300, apply a hook&loop patch on each side of the chassis bracket just outboard of the fuel tank rear mount.

4. Clean the mounting surfaces of the fuel tank with an approved cleaner and soft clean cloth and ensure that all dirt and debris has been removed.
5. Install rear strap by threading the narrow end rearward under the front seat bracket and the fuel tank rear mount and secure the strap by looping back forward onto the wider part of the strap or to the hook and loop patch.

NOTE

For Ninja 300, thread the narrow ends of the double strap rearward under the left and right sides of the chassis bracket and secure the straps by looping back forward onto the mating part of the straps.

NOTE

For Ninja 650 (2012-2013), Ensure rear strap does not pinch the fuel tank vent hoses. When installing seat, apply forward pressure to the front seat to lightly compress the tank bag rear strap, then the rear seat will have sufficient clearance to align with the seat locking bracket.

NOTE

The rear strap does not need to be removed when the tank bag is not being used. Magnets at the widest part will secure the strap and it can be used as a tank protector.

Tank Bag Installation

All Models except Concours 14

Hold the tank bag above the fuel tank and install the front strap clip to the front center part of the tank seam lip, then carefully pull the tank bag rearward and lower it to the fuel tank while keeping the front strap lightly snug and spreading the magnetic aprons outward on each side. Once the tank bag is installed, press the hook&loop rear tab onto the mating part of the rear strap.

Concours 14 (2010-2014)

Hold the tank bag above the fuel tank and install the two front strap rings to the left and right tank panel hooks, then carefully pull the tank bag rearward and lower it to the fuel tank while keeping the front straps lightly snug and spreading the magnetic aprons outward on each side. Ensure the rear magnetic flap is laying flat and centered on the fuel tank.

Tank Bag Features

1. Ports on front and back of tank bag can be used to route wires and hydration tubes.
2. D-rings and hook&loop side flaps allow storage of hydration tubes.
3. Front pocket can be used for small items and power cords.
4. Tank bag expansion zipper allows more storage if needed.
5. Lid tray can be used to store Toll Transponders when local or state laws require visible display of such devices.

Care and Cleaning

Clean the tank bag with mild soap and warm water. Do not use harsh abrasive cleaners. Cover the clear tray window when parked to minimize UV damage.