



700 S. Hathaway St. Unit E
Banning, CA. 92220
Web: <http://www.imsproducts.com>
Orders: (800) 237-9906
Information: (951) 653-7720
FAX: (951) 653-1060

Gas Gas
(21-22) MC 250F / 450F
EX250F / 350F / 450F
2.9 Gallons
IMS Tank ID: GG-4B
Part # 118804 / 218804

Also Fits EC250/300 and EX300
EFI Models, But ONLY With TPI
Fittings From IMS (P/N: 322150)

(21-22) MC125 (Carb Model)
(22) MC250 (Carb Model)

IMS Tank ID: GG-4A
2-Stroke Carb Model
Part# 118806/218806

IMS PARTS LIST

- (1) Fuel Tank
- (1) Gas Cap-322100-BLK*
- (1) SEAL-322101*
- (*Excluded on Dry-Break*)
- (4) Seat Hooks (BRK-SITWASH-S)
- (4) 5x18 Button Head
(MTP-7380105018)
- (7) 5x12 Allen Screws w/flange
(MTP-73801F05012)
- (1) Rear seat-hook bracket
(BRK-IMS-PLATE)
- (2) 5x12 Flat Allen Screws *3mm
allen*(MTP-7991105012)
- (1) 6x12 Button Head Screw *4mm
allen*(MTP-7380106012)

OEM ITEMS TO USE

- Shrouds
- Fuel Pump & Regulator (4-Stroke)
- Petcock (2-Stroke Carb Models)

WARNING!

Clean Tank Interior Thoroughly Before Installation. Install This Fuel Tank ONLY In a Well Ventilated Area, As Gasoline Fumes Are EXTREMELY Dangerous. DO NOT START OR OPERATE THE VEHICLE IF THERE ARE ANY FUEL LEAKS! IMS Recommends That Installation Be Done By a Licensed Mechanic. Read All Instructions First Before Beginning Installation.

TANK REMOVAL

Drain all fuel from OEM fuel tank into a government approved fuel container with a greater capacity than the fuel tank on vehicle.

Remove seat, shrouds, seat hook, tank bolt and center-mount bushing. Disconnect the power cable from the pressure regulator located at the back of the tank just under the seat. Disconnect the fuel line at the quick coupling below the left side of the tank by the throttle body. Remove OEM tank. Remove the 4 screws holding the pressure regulator. Unbolt the fuel pump on the left side by removing the fuel line & large cap nut. Remove the regulator & the attached pump.

TANK INSTALLATION

EFI Models Models: **To make installing the pump into the IMS tank easier, fish a safety wire or string from the large pump mounting hole to the regulator opening, attach the pull line to the large mounting stud of the pump.** Install the pump in the IMS tank, then regulator using (4) 5x18mm button head screws provided.

2-STROKE (CARB MODELS) ONLY (2) 5X18mm BUTTON HEAD SCREWS WILL BE USED TO INSTALL STOCK PETCOCK.

Both Models:

Mount tank on the bike, reconnect the fuel line & power cable to the regulator and install OEM center-mounting bushing & bolt. Attach the (2) Shroud hooks/Shoulder Washer with (2) 5 x 12mm screws w/flange, **These will slide into the grooves on the shrouds** Proceed to attach the top portions of the shrouds with (4) 5x12mm screws w/flange. **The rear left connection will require drilling the shroud with a 1/4" drill bit located at the position of the insert.**

Using (1) 5x12mm screw w/flange, attach (1) seat-shroud hook to the tank. just forward of the center mount, **this will act as the upper seat hook** **(See Illustration #1).**

Next, attach the provided "Rear seat-hook bracket" to the tank using (2) 5x12 flat allen screws. Finally, attach the last seat-shroud hook into the top of the "Rear seat-hook bracket" using (1) 6x12mm button head screw. ** This will act as the rear seat-hook **

Be sure that the tank is mounted securely and does not in any way inhibit the controls or function of the vehicle. Ensure that there are no sharp objects that rub against the tank that may eventually puncture the tank. Also, check that you have sufficient clearance from any heat source that could melt the fuel tank.

Add fuel to your **IMS** fuel tank. Always check for any fuel leaks before operating your bike, and enjoy your longer ride!

"FOR COMPETITION USE ONLY"

Legal in California ONLY for racing vehicles which may never be used upon a highway

DISCLAIMER: Due to uncontrolled variables in the manufacturing process of rotationally molded fuel tanks, the fuel tank may vary in size and shape by up to 7% of the manufacturer's original listed capacity

(See Illustration #1).

